U4GO is a high performance
UHF integrated 900MHz
system perfect for
vehicle and people identification

The AES128 encryption RF module works in two operating modes:

Stand-Alone Mode:

Manage up to 7,560 UHF credentials and 100 remote keys

or

Wiegand Mode (26-, 30- or 44-bit supported):

Maximum credentials management depends on the capacity of the access control system

NHVCO

U4GO provides secure long-range access for many applications such as parking facilities, gated communities, campuses and rolling stock.

The **U4GO** readers are easy to install, versatile, and perfectly suited for for all your needs.

Operating temperature from -10° to 140°F (-25° to 60°C)





www.cdvi.ca

U43GO

High Performance UHF Integrated System

Wireless Signal with AES128 ENCRYPTION







UHF READERS

A10U49 Long-Range Reader



- 33 ft (10 m) read range
- Compatible with Atrium,
 Centaur and most Wiegand systems
- 50 mph vehicle speed
- 17.5 x 17.5 x 2.15 in.

A6U49 Mid-Range Reader



- 20 ft (6 m) read range
- Compatible with Atrium, Centaur and most Wiegand systems
- 50 mph vehicle speed
- 9.25 x 9.25 x 2.25 in.

UHF CREDENTIALS

CTU48 ISO RFID Card



- Sold in packs of 10
- Available in dual technology (UHF + Mifare DESFire EV2 or other combo)

ATU48 Windshield RFID Tag



- Passive battery free tag
- Sold in packs of 10
- Flexible sticker

PTU48 License Plate RFID Tag



- Designed for vehicle tracking
- Dust and water resistance
- Sold individually



